(₿


PLOT SCALE: 1=1

DWG. SCALE:

A2413100

NOTES:

- 1. THIS IS A ULTRA- HIGH VACUUM COMPONENT (UHV)
- 2. WHEN MACHINING VACUUM PARTS, USE OF SILICONE AND SULPHUR-BASED CUTTING FLUIDS IS PROHIBITED. USE ONE OF THE FOLLOWING:
 - A) CIMCOOL 5 STAR 49 B) TRIM SOL
- 3. ALL SURFACES MUST BE MACHINED FOR CLEAN UP
- 4. FINISHING: WHEN MACHINING VACUUM PARTS USE OF ABRASIVE PAPER OR SANDING DISCS, BUFFING OR POLISHING COMPOUNDS, OR RESIN-BONDED GRINDING WHEELS IS PROHIBITED
- 5. CLEANING: THE COMPONENT MUST BE CLEANED SUCH THAT A UHV PRESSURE OF 1 X 10 -9 TORR CAN BE ACHIEVED
- 6. HANDLING: THE COMPONENTS SHALL BE HANDLED WITH WHITE SILK GLOVES AND WRAPPED WITH ALUMINUM FOIL TYPE DRY ANNEAL AND UNDER CLEAN ROOM CONDITIONS



SCALE 2X

